



Job Name: \_\_\_\_\_

Type: \_\_\_\_\_

Part #: \_\_\_\_\_

Notes: \_\_\_\_\_

# LSFLEDMR2

## LED FIXED OPTICS

### THERMOPLASTIC EMERGENCY UNIT

STANDARD



#### ILLUMINATION

- Long life, efficient, ultra bright white LED lamp heads.
- Two fixed, 2.0 watt LED lamp heads.
- High performance, chrome-plated metallized reflector and plastic lens for optimal light distribution.

#### ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 3.6V long life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

#### MOUNTING

- Universal knockout pattern on back plate for surface mount. Snaps into place making internal electrical connections.
- Suitable for wall or ceiling mount.


#### HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.

#### WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, cULus, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- CSA Listed to UL 924 standards for damp locations (0°C – 40°C).

#### DIMENSIONS



Sample Part Number: LSFLEDMR2

#### ORDERING INFORMATION

MODEL	HOUSING COLOR	
LSFLEDMR2	(blank) B	White Black