



Job Name: \_\_\_\_\_

Type: \_\_\_\_\_

Part #: \_\_\_\_\_

Notes: \_\_\_\_\_

# 4.

07000□



**STANDARD**



## ILLUMINATION

Long life, efficient, ultra bright white LED.  
 6W (2 LEDs x 3.0 watt) per unit.  
 Mirror-bright reflector and prismatic polycarbonate refractor.  
 Can be used as a Normally-ON or Normally-OFF light as well as on a switched circuit.

## ELECTRICAL

Dual 120/277 voltage.  
 Charge rate/power ON LED indicator light and push-to-test switch for mandated code compliance testing.  
 4.8V long life, maintenance-free, rechargeable NiCd battery.  
 Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination.  
 Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.  
 Self-diagnostic test feature continually diagnoses units performance and tests system to ensure reliable operation and to meet electrical and life safety codes.  
 Field-selectable wiring allows for AC operation of the unit to be controlled using a wall-switch or a photocell or any other switching mechanism.

LSLEDEMBEL-SDT  
 LSLEDEMBEL-SDT-CW

## HOUSING

Decorative, Low Profile, architectural design.  
 Die-cast aluminum housing.  
 Durable powder-coated finishes in white, black, nickel and dark-bronze.  
 Sealed and gasketed.

## MOUNTING

Surface mount via easy connect back plate that fits most standard size junction boxes.  
 Universal K/O pattern on back plate for wall mount.  
 Threaded opening at the top of the enclosure for conduit mount.


## OPTIONS

CW: Optional internal heater for extreme cold temperature applications (-20°C - 50°C).  
 PC: Unit features optional photocell technology that automatically responds to low exterior lighting levels in AC mode.

## LISTINGS AND WARRANTIES

Five year warranty on all electronics and housing. Battery prorated for two years.  
 Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.  
 UL Listed for wet locations (-20°C - 50°C).

## DIMENSIONS



## SPACING

## ORDERING INFORMATION

Sample Part Number: LSLEDEMBEL

MODEL	HOUSING COLOR		OPTIONS
LSLEDEMBEL	W - White B - Black BR - Dark Bronze N - Nickel	SDT - Self-Diagnostics (standard)	CW - Cold Weather PC - Photocell Sensor