



Job Name: _____

Type: _____

Part #: _____

Notes: _____

LSLEDM7W

RECESSED LED EMERGENCY UNIT

ILLUMINATION

Two fully adjustable 1.0W white LED lamp heads. High performance chrome-plated metal reflectors and plastic lens for optimal light distribution.

ELECTRICAL

Dual 120/277 voltage. Charge rate/power ON LED indicator light and push-to-test switch for mandated code compliance testing. LVD (low voltage disconnect) prevents battery from deep discharge. 6V maintenance-free, rechargeable sealed lead acid battery. Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination. Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

Bar hangers on the back box for recessed mount. Compatible with drop ceiling mount installations.

HOUSING

Durable 20-gauge steel trim plate in white or black finish. Trim securely attached to housing with spring clips.

LISTINGS AND WARRANTIES

Five year warranty on all electronics and housing. Battery prorated for two years. Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes. UL Listed for dry locations (25°C).

DIMENSIONS

ORDERING INFORMATION

Sample Part Number: LSLEDM7W

MODEL	HOUSING COLOR	OPTIONS
LSLEDM7W	Blank - White B - Black	

Special voltage options available. Check with your Lighting Representative.