



Job Name: _____

Type: _____

Part #: _____

Notes: _____

LSLEDMWL

WET LOCATION REMOTE CAPABLE LED EMERGENCY UNIT

ILLUMINATION

Sealed and gasketed weather proof lamp heads with high performance chrome-plated metallized reflector and tempered glass lenses for optimal light distribution.
Long lasting efficient ultra bright white LED lamp heads.
1.875W (15 LEDs x 0.125) per head.

ELECTRICAL

Dual 120/277 voltage.
Charge rate/power ON LED indicator light and push-to-test switch for mandated code compliance testing.
9.6V long life, maintenance-free, rechargeable NiCd battery.
Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination.
Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.
Remote capacity of 3.7W standard in operating temperatures of 0°C - 50°C.

MOUNTING

External mounting brackets for simplified wall mounting.

HOUSING

Corrosion-resistant 5VA flame retardant UV-stabilized polycarbonate in gray or black finish.
Sealed and gasketed housing with hinged cover.
Sealed test switch.

LISTINGS AND WARRANTIES

Five year warranty on all electronics and housing. Battery prorated for two years.
Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
UL Listed for wet locations (-20°C - 50°C).

DIMENSIONS

ORDERING INFORMATION

Sample Part Number: LSLEDMWL

MODEL	HOUSING COLOR
LSLEDMWL	Blank - Gray B - Black

Special voltage options available.
Check with your Lighting Representative.

NOTE: Product specifications subject to change without notice. Updated 08.2017