



Job Name: \_\_\_\_\_

Type: \_\_\_\_\_

Part #: \_\_\_\_\_

Notes: \_\_\_\_\_

# LSLEDR HL HIGH LUMEN LED EMERGENCY UNIT

## ILLUMINATION

Long lasting, efficient ultra bright white LED lamp heads.  
1.7W (8 LEDs x 0.2125) per head.  
High performance chrome-plated metallized reflector and plastic lens for optimal light distribution.  
Adjustable LED lamp heads provides optimal center-to-center-spacing.

## ELECTRICAL

Dual 120/277 voltage.  
Charge rate/power ON LED indicator light and push-to-test-switch for mandated code compliance testing.  
3.6V long life, maintenance-free, rechargeable NiCd battery.  
Internal solid-state transfer switch automatically connects the internal battery to LED lamp heads for minimum 90-minute emergency illumination.  
Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

## MOUNTING

Surface mount via easy connect back plate, which fits most standard junction boxes and snaps into place making internal electrical connections.  
Top and side knockout for conduit applications.  
Suitable for wall or ceiling mount.

## HOUSING

Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.

## LISTINGS AND WARRANTIES

Five year warranty on all electronics and housing. Batteries provided for five years.  
UL Listed for damp locations (0°C - 40°C).  
Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

## DIMENSIONS

## ORDERING INFORMATION

Sample Part Number: LSLEDRX5HL

MODEL	HOUSING COLOR	OPTIONS
LSLEDRX5HL	Blank - White B - Black	

Special voltage options available. Check with your Lighting Representative.