



Job Name: _____

Type: _____

Part #: _____

Notes: _____

LSM AD USTA LE RECESSED EMERGENCY DOWN LIGHT UNIT

ILLUMINATION

Adjustable ultra bright 8W bi-pin halogen lamp head.
Sealed beam PAR36-type gimbal trim with smooth chromeplated-metallized reflector and plastic lens offers optimal light distribution.

ELECTRICAL

Dual 120/277 voltage.
Charge rate/power ON LED indicator light and push-to-test switch for mandated code compliance testing.
LVD (low voltage disconnect) prevents battery from deep discharge.
6V maintenance-free, rechargeable sealed lead acid battery.
Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination.
Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

Compatible with drop ceiling mount installations. Bar hangers included.

HOUSING

Steel mounting frame and housing.
6" recessed housing with mounting bar hangers.
Impact-resistant thermoplastic adjustable gimbal trim.
Junction box with 3/4" knockouts for AC input.
Trim securely attached to housing with spring clips.

LISTINGS AND WARRANTIES

Five year warranty on all electronics and housing. Battery prorated for two years.
Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
UL Listed for dry locations.

DIMENSIONS

ORDERING INFORMATION

Sample Part Number: LSM9

MODEL	HOUSING COLOR	
LSM9	Blank - White B - Black	GIMBAL

Special voltage options available. Check with your Lighting Representative.